

The PD3000U is widely known as the market leading pole display for PC-based POS systems. It has long set the standard for reliability, value and functionality - reasons why most value-added resellers ask for it and other Logic Controls pole displays by name.

Technical Information

Display Method: Vacuum Fluorescent Display (VFD)

Display Color: Green

Number of Characters: 20x2

Brightness: 690 cd/m²

Character Font: 5 x 7 Dot Matrix

Character Type: ASCII

Character Size: 3.5mm x 5.0mm

Character Pitch: 5.0 mm

Reliability: 300000 Hour(s) MTBF

Command Set: Logic Controls

Interfaces/Ports: USB

Input Voltage: 120 V AC

Physical Characteristics

Dimensions: 3.37" (86mm) x 7.87" (200mm) x x 1.75" (44mm) - Fluorescent Display

2.00" (51mm) x 2.12" (54mm) x x 2.25" (57mm) - Rectangular Base

0.90" (23mm) x 4.00" (102mm) x x 8.00" (203mm) - Base Plate

Weight: 2.7 lb (1.22 kg)

Color: Black

Shipping Information

Shipping Weight : 4.18 lb

Shipping Dimensions : 4.0" Height x 10.0" Width x 28.0" Depth

Environmental Conditions

Temperature: 0°C (32°F) to 50°C (122°F) Operating

-20°C (-4°F) to 70°C (158°F) Storage

Humidity: 85% Operating Non-condensing

90% Non-operating Non-condensing

Miscellaneous

Package Contents: PD3000U Pole Display

Power Adapter

6 Foot Cable

Warranty

Manufacturer Warranty: 1 Year(s) Limited