

The PD3900 is widely known as the market leading pole display for PC-based POS systems. It has long set the standard for reliability, value and functionality- reasons why most value-added resellers ask for it and other Logic Controls pole displays by name.

#### Technical Information

Display Method: Vacuum Fluorescent Display (VFD)

Display Color: Green

Number of Characters: 20x2

Brightness: 690 cd/m<sup>2</sup>

Character Font: 5 x 7 Dot Matrix

Character Type: ASCII

Character Size: 3.5mm x 5.0mm

Character Pitch: 5 mm

Reliability: 300000 Hour(s) MTBF

Command Set: Logic Controls

OPOS

JPOS

Interfaces/Ports: Power USB

Input Voltage: 6 V AC

Input Voltage Range: 120 V AC

#### Physical Characteristics

Dimensions: 3.37" (86mm) x 7.87" (200mm) x 1.75" (44mm) - Fluorescent Display

2.00" (51mm) x 2.12" (54mm) x 2.25" (57mm) - Rectangular Base

0.90" (23mm) x 4.00" (102mm) x 8.00" (203mm) - Base Plate

Weight: 2.7 lb (1.22 kg)

Color: Black

#### Shipping Information

Shipping Weight : 3.6 lb

Shipping Dimensions : 3.6" Height x 10.0" Width x 28.0" Depth

#### Environmental Conditions

Temperature: 0°C (32°F) to 50°C (122°F) Operating

-20°C (-4°F) to 70°C (158°F) Storage

Humidity: 85% Operating Non-condensing

90% Storage Non-condensing

Agency Approvals

Agency Approvals: FCC Class A

#### Miscellaneous

Package Contents: PD3900 Pole Display

Power Adapter

#### Warranty

Manufacturer Warranty: 1 Year(s)